

phone
1-800-628-3603

web
www.RedyRef.com

email
Sales@RedyRef.com



SKYLINE 2.0 HARDWARE

Standard sizes:
43" and custom sizes available;
Dual sided option

Ideal for transactional applications like ticketing, payment, dispensing or digital signage. Indoor or Outdoor ready.

With its crisp, clean lines and portrait-style orientation, the Skyline freestanding kiosk was designed with proportions reminiscent of a sleek high-rise skyscraper. Although it is one of our most popular designs for outdoor ticketing and payment transactions, it is an excellent choice for a variety of other applications both indoor and outdoor. This includes interactive wayfinding across large office and hospital campuses, "smart city" placement in bustling metropolitan areas, and in transportation hubs, such as train stations and airports.

The Skyline's generous display size lends itself to easy end-user interaction, including the option to add a dual sided 49" display. The modularity of this kiosk offers a variety of component configurations which included: ticket printing, card payment device (EMV, swipe, insert, NFC), barcode scanner, audio - all with outdoor capability.

Whether configured with a touch or non-touchscreen display, the Skyline makes a bold statement across environments, from outdoor transactional kiosks in busy cities, to directories in indoor multi-building campuses.

Also available:

- Custom branding including silkscreen, decal and vinyl wraps
- Optional component integrations (see p. 2 tech specs)
- Touch (interactive) or non-touch (static) displays
- Dual sided



ADA COMPLIANT
ISO 9001:2015 CERTIFIED

THE REDYREF CLIENT PORTFOLIO PROUDLY INCLUDES:



SKYLINE 2.0

STANDARD

OPTIONAL

ELO COMPATIBLE

Touch Monitor:
42.5" (4343L)

	SKYLINE 2.0 - SPECIFICATION	OD4155-SS
Description	Configuration	Free Standing
	Number of Displays	1 (option for dual sided)
	Side A	43" LCD (portrait orientation)
Connectivity	Operating Platform	Solid State Media Player (Windows, Android, Linux)
	Internet	RJ45 Data Cable (or Wireless Option)
Printing	Printer	Boca Lemur-K (or similar)
Payment Processing	Payment	Ingenico i-Series or i-Series Combo (or similar)
Audio	Speakers with Amp	30 Watt - Volume Control
	Microphone	
Video	Webcam	HD Webcam
Enclosure	Finish	Steel Construction Throughout Exterior (Outdoor Stainless Steel; Powder Coating Optional)
	Thermal Management (Outdoor only)	HVAC Compartment and Powered Air Curtain
	Protective Glass (Outdoor only)	5MM Tempered Glass
	Mounting	Mount to floor with Anchor Bolts (option for non-anchored base plate)
	Accessibility	Security Key Locking Mechanism
	Dimensions (H x W x D)	73"H x 35"W x 11-3/16"D
	Weight	250lbs
Display	Display	43" LCD (Dual Dided Option 49" LCD)
	Native Resolution	1920 x 1080
	Brightness	350 cd/m2 (outdoor 2,500 cd/m2, Anti-glare, illumination sensor)
	Touch (optional)	Multi-Touch Protective Capacitive

SKYLINE 2.0

 STANDARD

 OPTIONAL

ELO COMPATIBLE

Touch Monitor:
42.5" (4343L)

	SKYLINE 2.0 - SPECIFICATION	OD4155-SS
Other Features	Software	Kiosk Management Software
	Monitoring	Kiosk Monitoring Software
	Scanning	Bar Code Scanner
	UPS	900 Watt Back Up Power Supply
	Signage	Backlit Illuminated
	Branding	Silkscreen or Decal Wrap
	Audio Jack	Input Audio
	USB Connector	Input USB
Power	Input Range	100 to 240 V 50/60 Hz
	Draw	(1) 15 Amp or 20 Amp Circuits (depending on final component config)
	Termination	Hardwired Duplex Receptacle thru Base Plate or Plug in Rear of Kiosk
Environment	Operating Temp	Indoor = 32F to 100F; Outdoor = Minus 22F to 130F
Warranty	1 Year	Manufacturers Limited Warranty
	On-Site and Extended Warranty Available	